AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS:

- 1. (CURRENTLY AMENDED) A clamp, said clamp including:
 - a base;
 - a handle connected to said base;
 - a pin rotatably supported within said handle;
 - a bracket pivotally arranged with respect to said handle;
- a lever having an orifice through a surface, one end of said bracket arranged through said orifice; and
 - a spring arranged between said handle and said pin.
- 2. (PREVIOUSLY PRESENTED) The clamp of claim 1 wherein said lever contacting said pin and said bracket and said lever having an orifice through a surface.
- 3. (ORIGINAL) The clamp of claim 1 wherein said handle having a first and second member.
- 4. (ORIGINAL) The clamp of claim 3 wherein said pin having a projection extending therefrom.

- 5. The clamp of claim 4 further including a fastener arranged (ORIGINAL) between said first and second member of said handle. The clamp of claim 1 wherein said spring will hold said 6. (ORIGINAL) bracket in a predetermined position when the clamp is open. 7. The clamp of claim 2 wherein said lever is arranged on one (ORIGINAL) or both sides of said handle. The clamp of claim 5 wherein said spring contacts said 8. (ORIGINAL) fastener on one end and said projection on an opposite end. The clamp of claim 8 wherein said spring is arranged in a 9. (ORIGINAL) space defined in part by said first and second member. 10. (ORIGINAL) The clamp of claim 1 wherein said base having a first and second member.
- 11. (CURRENTLY AMENDED) A manual pull action clamp, said clamp including:

a base;

a handle including a first and second portion, said handle pivotally connected to said base;

a pin arranged therebetween said first and second portions of said handle, said pin having a cylindrical projection extending from a surface thereof;

- a bracket secured to said pin;
- a lever having a generally L-shape and an orifice through a surface thereof; and a spring arranged between said handle and said pin.
- 12. (PREVIOUSLY PRESENTED) The clamp of claim 11 wherein said lever arranged near one end of said bracket.
- 13. (CURRENTLY AMENDED)

 A manual pull action clamp, said clamp including:

a base;

a handle including a first and second portion, said handle pivotally connected to said base;

a pin arranged therebetween said first and second portions of said handle;

<u>a bracket secured to said pin</u>, said bracket having a U-shape and secured to said pin on both ends thereof;

a lever having a generally L-shape and an orifice through a surface thereof; and a spring arranged between said handle and said pin.

The clamp of claim 11 wherein

14. (CANCELLED)

- 15. (ORIGINAL) The clamp of claim 14 wherein said first and second portion having a fastener arranged therebetween.
- 16. (ORIGINAL) The clamp of claim 15 wherein said spring is arranged between said first and second portion.
- 17. (ORIGINAL) The clamp of claim 16 wherein said spring is secured to said fastener on one end and to said projection on an opposite end.
- 18. (ORIGINAL) The clamp of claim 11 further including a latch plate contacting said bracket when the clamp is in a closed position.
- 19. (ORIGINAL) The clamp of claim 11 wherein said base having a first and second member.
- 20. (PREVIOUSLY PRESENTED) A manual toggle locking pull action clamp, said clamp including:
 - a base having a plurality of orifices therethrough;
- a handle having a first and second member, said handle pivotally connected to said base, said handle having a fastener arranged between said first and second member;
- a cylindrical rod pivotally arranged between said first and second members of said handle;

a latch member secured to said rod, said latch member pivots with respect to said handle;

- a pin extending from a surface of said rod;
- a spring secured to said pin on one end and to said fastener on an opposite end;
- a tab lever arranged over at least one end of said latch member; and
- a latch plate contacting said latch member when the clamp is in a closed position.